

IITDh/IPS/2025-26/LPC/268
28th January 2026

Invitation for Quotation

Name of the Work: Supply of dewatering motors and high pressure washers

Location: Permanent Campus IIT Dharwad

With reference to the aforementioned work, quotations are hereby invited for the said work. Interested vendors with experience in said works can submit their quotes (*as per Annexure-I*) on their official letterhead, duly attested, **in a sealed envelope via post / courier** to the following address:

To,
IPS Office (NE-113),
First Floor Admin Block,
Indian Institute of Technology Dharwad,
Permanent Campus, Chikmalligwad.
Dharwad-580011.

Deadline for submission: 11th February 2026 up to 1300 hours

NOTE:

- Any quotes received after 1300 hours on 11/02/2026 will not be accepted.
- Name of the Work / LPC number and Firm name should be mandatorily written on the sealed cover.

Sd/-
Executive Engineer
Indian Institute of Technology Dharwad

Annexure -1

BoQ for Motors for Dewatering and High Pressure wash (Asset Type)					
Sl.no	Item Type & Description	Make Details	Qty Reqd	Rate/Unit	Total
1	600 MA 0.75 HP Sewage Submersible Pump Phase: Single Phase Model No: FEKA 600 MA Type of Product: Sewage Submersible Pump Application: Suitable for lifting sewage water from cesspools, and is capable of handling suspended solid matter with size up to 25 mm. Adaptable to different emergency situations, Element product and durability, Automatic operation guaranteed, Easy to use Pump Impeller & Shaft: Vortex Pump Housing: Stainless Steel Solid Handling Capacity: 25 mm Flow: 7.45-2.2 m ³ /hr Speed (RPM): 2800Suc x Del (mm): 25x25 mm Head: 16 mPower: 0.75 HP	Grundfos / Kirloskar / Xylem	2		
2	2 HP Submersible Dewatering Pump Three Phase Voltage: 415 V Phase: 3 Phase Type of Product: Submersible Dewatering Pump Power Rating: 1.5 Kw Weight: 18 Kg Flow Rate: 650 LPM Dimension: 21.25 x 21.25 x 52.5 cm Head: 16 mPower (HP): 2 HP	Grundfos / Kirloskar / Xylem / Cosmos	2		
3	3 HP Submersible Dewatering Pump Three Phase - CDW33L Voltage: 415 V Frequency: 50 Hz Phase: 3 Phase Type of Product: Submersible Dewatering Pump Power Rating: 2.2 kW Weight: 32 Kg Flow Rate: 700 LPM Dimension: 23.75 x 23.75 x 72.5 cm Head: 16 mPower (HP): 3 HP	Grundfos / Kirloskar / Xylem / Cosmos	2		
4	Aquatak 125 1500-Watt High Pressure Washer Maximum Pressure 125 Bars, Item Weight 6000 Grams, Hose Length 5 Metres, Specification Met CSA, Product Dimensions 14.4L x 14.2W x 17.3H Centimeters Maximum Flow Rate 360 Liters Per Hour, Manufacturer Model 06008A7A70, Item model number 06008A7A70, Manufacturer Part Number 06008A7A70 Volume 55451 Millilitres Material Plastic Size Medium Assembly Required No Voltage 240 Volts Wattage 1.5 Watts Including: 1. High Pressure Washer - Self Priming Kit - Easy Aquatak 110 & 120, Universal Aquatak 125 & 130, Advanced Aquatak 140 & 160 2. Extension Hose 6m	BOSCH / Stanley / V-Guard	1		
SUB TOTAL ₹					
GST ₹					
Total ₹					

(Contractors Sign and Seal)

